

ACTION MEMORANDUM CHATFIELD WATERSHED AUTHORITY

Date: April 17, 2023

TO: CWA Board

FROM: Alan J. Leak, P.E., CWA Technical Consultant

SUBJECT: Lynker's Chatfield Watershed Model – Point Source Model Results Memorandum dated March 30, 2023.

SUMMARY OF ACTION REQUESTED: Accept Lynker's Chatfield Watershed Model – Point Source Model Results Memorandum dated March 30, 2023.

RECOMMENDED EFFECTIVE DATE: Not Applicable

COST IMPACTS: No cost impacts

PURPOSE / BACKGROUND: The CWA contracted with Lynker to use the Authority's Watershed model (prepared by Lynker) to perform additional model runs to investigate the potential changes in phosphorus loads and concentrations entering Chatfield Reservoir from changes in phosphorus loads from wastewater treatment facilities in the Chatfield watershed. The attached Memorandum presents and documents the assumptions, analysis, and results of Lynker's modeling. This memorandum completes Lynker's contracted modeling tasks.

RECOMMENDATION(S): Recommend the CWA TAC Board Approve Lynker's Chatfield Watershed Model – Point Source Model Results Memorandum

Attachment: Lynker Chatfield Watershed Model – Point Source Model Results Memorandum dated March 30, 2023.

MEMORANDUM

To: Chatfield Watershed Authority Technical Advisory Committee
cc: Diane Kielty, Colorado Watershed Assembly; Alan Leak, RESPEC
From: Bill Szafranski, Lynker Technologies
Subject: Chatfield Watershed Model – Point Source Model Scenarios
Date: March 30, 2023

Introduction

The Chatfield watershed model was built to simulate total phosphorus loading in the Chatfield watershed. The model was built in 2016 using the Hydrologic Simulation Program – FORTRAN (HSPF) and was set up to run from January 1, 1995 to September 30, 2015 at an hourly time step. The model was calibrated using water quality records from 2000 to 2015. The model currently simulates five point source discharges in the watershed: Plum Creek Water Reclamation Authority (PCWRA), Lockheed Martin, Sageport wastewater treatment facility (WWTF), Waucondah WWTF, and the Roxborough WWTF (see Figure 1). In most instances the point sources are simulated in the model from 2000 to 2015 using average monthly data. The Louviers and Town of Larkspur WWTFs were not included in the model because they had not recently discharged to the watershed when the model was built (Leonard Rice Engineers and Lynker Technologies, 2016).

Purpose

In this analysis, we evaluate the impact of changes to the point source discharges in the watershed by simulating the point source discharges a) off and b) increased to the full wasteload allocation. In the first analysis, to evaluate the impact of these point sources on total phosphorus loading in the Chatfield Reservoir watershed, we ran the model with these five point source discharges turned off and compared the results to the watershed model representing historical conditions (point sources following historical operations). In the second analysis, we ran the model with the point source dischargers set to their full wasteload allocation and we compared the results with the watershed model representing historical conditions.

Point Source Observational Data

For each of the point sources, we calculated average monthly orthophosphorus and organic phosphorous loads from available observational total phosphorus data. The observational data were collected at different frequencies and durations for each of the point sources, as summarized below.


- The Plum Creek Water Reclamation Authority (PCWRA) is located on East Plum Creek at Highway 85 and West Happy Canyon Road, and the data are loaded into the model in reach 52. The PCWRA total phosphorus point source data typically include four to five data points per month between January 2000 and October 2012 and one data point per month between November 2012 and July 2015, with average monthly values used from August 2015 to September 2015.

- The Lockheed Martin facility discharges to the South Platte River near Waterton Canyon, and the data is loaded into the model in reach 16. The Lockheed Martin total phosphorus point source data typically include four data points per month from January 2000 to October 2007 and one data point per month from November 2007 to June 2015, with average monthly values used from July 2015 to September 2015.
- The Sageport wastewater treatment facility (WWTF) discharges to East Plum Creek, and the data is loaded into model reach 116. The Sageport point source data include one total phosphorus measurement per month from January 2005 to December 2014, with data from 2009 and 2015 filled using average monthly values.
- The Waucondah WWTF discharges into Bear Creek, a tributary to West Plum Creek, and the data is loaded into model reach 113. The Waucondah point source data include one total phosphorus measurement per month from January 2005 to December 2014, with data from 2015 filled using average monthly values. This data was used to calculate average monthly orthophosphorus and organic phosphorus loads to use in the model.
- The Roxborough WWTF is located near the South Platte River, and the data are loaded into model in reach 29. The Roxborough point source data typically includes 4 to 5 data points per month from January 2000 to September 2007, except for September through December 2001 and all months in 2003, which were filled using average monthly values. Roxborough stopped discharging into the Chatfield watershed after 2007 when it conveyed its effluent to the Littleton Englewood WWTF (Leonard Rice Engineers and Lynker Technologies, 2016).

A summary of the annual total phosphorus point source loads included in the model is provided in Table 1.

Table 1: Annual Total Phosphorus Point Source Load

| Year | PCWRA (lbs) | Lockheed Martin (lbs) | Sageport WWTF (lbs) | Waucondah WWTF (lbs) | Roxborough WWTF (lbs) |
|-----------------------------------|--------------|-----------------------|---------------------|----------------------|-----------------------|
| 2000 | 1,250 | 310 | 0 | 0 | 480 |
| 2001 | 1,630 | 140 | 0 | 0 | 450 |
| 2002 | 2,650 | 190 | 0 | 0 | 550 |
| 2003 | 3,310 | 180 | 0 | 0 | 770 |
| 2004 | 3,910 | 200 | 0 | 0 | 830 |
| 2005 | 2,650 | 230 | 62 | 103 | 1,180 |
| 2006 | 2,300 | 170 | 66 | 107 | 760 |
| 2007 | 2,180 | 280 | 51 | 144 | 970 |
| 2008 | 2,660 | 80 | 53 | 209 | 0 |
| 2009 | 2,880 | 20 | 47 | 101 | 0 |
| 2010 | 1,850 | 20 | 40 | 93 | 0 |
| 2011 | 2,210 | 10 | 34 | 81 | 0 |
| 2012 | 2,510 | 10 | 25 | 69 | 0 |
| 2013 | 1,860 | 20 | 25 | 85 | 0 |
| 2014 | 1,900 | 20 | 29 | 91 | 0 |
| Average (when discharging) | 2,380 | 120 | 43 | 105 | 750 |



Source: Figure 2-12 (Leonard Rice Engineers and Lynker Technologies, 2016)

Figure 1: Point Source Locations

Watershed Simulated without Point Source Discharges

We used the Chatfield watershed model to run scenarios with the point sources operating normally (the historical model) and with the point sources turned off. When the point sources are turned off, all five point sources (PCWRA, Lockheed Martin, Sageport WWTF, Waucondah, and Roxborough WWTF) no longer discharge flow, total phosphorus, and other water quality constituents into the watershed.

We ran the model for the full period of record (January 1995 to September 2015) and analyzed the results from January 2000 to December 2014, representing the calibrated model record. Here we provide simulated annual total phosphorus loads for the South Platte (model reach 16) and Plum Creek (model reach 15) (Table 2). On average, the total phosphorus contribution from the South Platte River decreased by 360 pounds per year and the total phosphorus contribution from Plum Creek decreased by 1,740 pounds per year when the model simulates the watershed without point source discharges.

Table 2: Simulated Annual Total Phosphorus Load

| Year | South Platte River Total Phosphorus Load (lbs) | | | Plum Creek Total Phosphorus Load (lbs) | | |
|----------------|---|----------------------|------------|--|----------------------|--------------|
| | Historical Model | Point Sources Off | Difference | Historical Model | Point Sources Off | Difference |
| 2000 | 5,610 | 5,030 | 590 | 4,110 | 3,370 | 750 |
| 2001 | 3,010 | 2,700 | 310 | 4,100 | 3,080 | 1,020 |
| 2002 | 3,550 | 3,090 | 450 | 3,090 | 1,390 | 1,700 |
| 2003 | 7,440 | 6,800 | 640 | 10,630 | 8,270 | 2,350 |
| 2004 | 7,050 | 6,330 | 720 | 6,870 | 3,990 | 2,880 |
| 2005 | 8,730 | 7,760 | 960 | 6,720 | 4,630 | 2,080 |
| 2006 | 4,310 | 3,710 | 600 | 5,610 | 3,920 | 1,690 |
| 2007 | 17,090 | 16,130 | 960 | 19,190 | 17,340 | 1,850 |
| 2008 | 4,020 | 3,940 | 70 | 5,110 | 3,070 | 2,040 |
| 2009 | 5,320 | 5,300 | 20 | 7,750 | 5,590 | 2,170 |
| 2010 | 4,860 | 4,850 | 20 | 15,260 | 13,840 | 1,420 |
| 2011 | 1,590 | 1,580 | 10 | 4,960 | 3,400 | 1,560 |
| 2012 | 680 | 680 | 10 | 4,420 | 2,690 | 1,730 |
| 2013 | 2,060 | 2,040 | 10 | 4,010 | 2,750 | 1,260 |
| 2014 | 5,950 | 5,920 | 20 | 5,070 | 3,710 | 1,370 |
| Average | 5,420 | 5,060 | 360 | 7,130 | 5,400 | 1,720 |

Full Wasteload Allocation Simulation

We used the Chatfield watershed model to run scenarios with four of the five point sources discharging their full wasteload allocation to represent future potential buildout conditions in the Chatfield Reservoir watershed. In this scenario the Roxborough WWTF point source does not discharge into the watershed due to a change in wasteload ownership (Table 3). In Table 3, we show the total phosphorus load from the last 10-years of the historical record in the model (2005-2014), which is used in the development of parameters for the wasteload allocation scenario. We note that the total phosphorus load in the 10-year historical record (2005-2014) is similar to the total phosphorus load for the most recent historical data (2021), representing a reasonable approximation of current conditions. The total phosphorus load simulated by the model in the wasteload allocation scenario is 5,699 pounds (lbs)/year (as shown in Table 3), which represents 75% of the total phosphorus wasteload allocation for all point sources in the watershed (7,605 lbs/year) (CWA, 2021).

Table 3: Total Phosphorus Annual Historical and Wasteload Allocation

| Permittee | CDPHE Permit | Total Phosphorus Load (2005-2014) (lbs/yr) | Total Phosphorus Load (2021) (lbs/yr) | Total Phosphorus Wasteload Allocation (lbs/yr) |
|--|--------------|--|---------------------------------------|--|
| Plum Creek Water Reclamation Authority (PCWRA) | CO0038547 | 2,035 | 2,044 | 4,256 |
| Lockheed Martin Space Systems Company | CO0001511 | 57 | 22.1 | 1,005 |
| Perry Park Water and Sanitation District (Sageport) | CO0043044 | 41 | 59.4 | 73 |
| Perry Park Water and Sanitation District (Waucondah) | CO0022551 | 107 | 173.8 | 365 |
| Total | | 2,241 | 2,299 | 5,699 |

Note: The Roxborough WWTF stopped discharging to the watershed in 2007, and its wasteload allocation is owned by the Dominion Water and Sanitation District, which was not modeled for this analysis.

The wasteload allocation modeling scenario simulates an increase of approximately 3,458 pounds of total phosphorus per year compared to the 10-year historical average (2005-2014), of which about 950 pounds are distributed to the South Platte River and 2,500 pounds are distributed to Plum Creek (see Table 4).

Table 4: Total Phosphorus Wasteload Allocation by River Basin (lbs)

| Watershed | Wasteload Allocation | Historical (2005-2014) | Difference |
|--------------|----------------------|------------------------|--------------|
| South Platte | 1,005 | 376 | 629 |
| Plum Creek | 4,694 | 2,183 | 2,511 |
| Total | 5,699 | 2,559 | 3,458 |

The total phosphorus load is the product of concentration and flow volume. Therefore, when simulating the wasteload allocation we evaluated increases to total phosphorus concentrations and flow. For this analysis, we assumed that future total phosphorus concentrations would remain similar to historical total phosphorus concentrations, as dischargers are trying to meet concentration limits, so the increase in total phosphorus load is simulated by an increase in the total effluent (total flow) from the facility.

The historical total phosphorus concentrations and flow for each facility from the last 10 years of the historical record available in the model (2005-2014) are shown in Table 5 along with the modified total phosphorus concentrations and flow for the full wasteload allocation scenario. The average historical total phosphorous concentrations (2005-2014) were used as the basis of the total phosphorus concentrations in the wasteload allocation scenario. For each facility, historical and wasteload total phosphorus concentrations are similar while flows have been increased, contributing to the increase in total phosphorus load. The total phosphorus concentrations and flows from Table 5 were used to calculate a monthly total phosphorus load for each point source (Table 6), which sum to the total phosphorus annual wasteload allocation shown in Table 3 (5,699 pounds).

Table 5: Simulated Total Phosphorus Annual Wasteload Allocation

| Point Source | Historical Data (2005-2014) | | Wasteload Allocation Scenario | |
|--|---------------------------------------|---------------------------|---------------------------------------|---------------------------|
| | Total Phosphorus Concentration (mg/L) | Flow (ft ³ /s) | Total Phosphorus Concentration (mg/L) | Flow (ft ³ /s) |
| Plum Creek Water Reclamation Authority (PCWRA) | 0.22 | 4.70 | 0.22 | 9.87 |
| Lockheed Martin Space Systems Company | 0.16 | 0.19 | 0.16 | 3.22 |
| Perry Park Water and Sanitation District (Sageport) | 0.24 | 0.23 | 0.26 | 0.71 |
| Perry Park Water and Sanitation District (Waucondah) | 0.30 | 0.07 | 0.31 | 0.12 |

Table 6: Total Phosphorus Monthly Wasteload Allocation (lbs)

| Month | PCWRA | Lockheed | Sageport | Waucondah | Roxborough | Total |
|--------------|--------------|--------------|-----------|------------|------------|--------------|
| January | 361 | 85.4 | 6.1 | 30.4 | 0 | 483 |
| February | 326 | 77.1 | 6.1 | 30.4 | 0 | 440 |
| March | 361 | 85.4 | 6.1 | 30.4 | 0 | 483 |
| April | 350 | 82.6 | 6.1 | 30.4 | 0 | 469 |
| May | 361 | 85.4 | 6.1 | 30.4 | 0 | 483 |
| June | 350 | 82.6 | 6.1 | 30.4 | 0 | 469 |
| July | 361 | 85.4 | 6.1 | 30.4 | 0 | 483 |
| August | 361 | 85.4 | 6.1 | 30.4 | 0 | 483 |
| September | 350 | 82.6 | 6.1 | 30.4 | 0 | 469 |
| October | 361 | 85.4 | 6.1 | 30.4 | 0 | 483 |
| November | 350 | 82.6 | 6.1 | 30.4 | 0 | 469 |
| December | 361 | 85.4 | 6.1 | 30.4 | 0 | 483 |
| Total | 4,256 | 1,005 | 73 | 365 | 0 | 5,699 |

South Platte Historical Diversions

In the South Platte River, to quantify the total phosphorus load from point sources that reach Chatfield Reservoir, we needed to thoroughly document modeled historical diversions in the watershed. In the historical model, the Roxborough WWTF point source discharges into model reach 29 from 2000-2007, with discharges ending in 2007. In the same model reach (reach 29), there are two diversions (Denver Conduit #20 and Highline Canal) that divert water out of the watershed using historical diversion data. These diversions also remove total phosphorus from the watershed. In the historical model, they divert on average 2,690 pounds of total phosphorus annually (2000-2014) and in the point sources off scenario they divert on average 2,540 pounds of total phosphorus annually (2000-2014), about 140 less pounds. The difference in total phosphorus between these two diversions occurs from 2000 to 2007, when the Roxborough WWTF point source is active. Therefore, this difference needs to be accounted for when comparing the full wasteload allocation scenario to the historical scenario. Since the Roxborough WWTF point source is always off in the full wasteload allocation scenario, the difference in total phosphorus from the diversions needs to be accounted for when tracking the transport of total phosphorus in the watershed. See the *Discussion of Results* Section of this memorandum for a discussion of how this difference is accounted for in the model results.

Results

We ran the model for the full period of record (January 1995 to September 2015) and analyzed the results from January 2000 to December 2014, representing the calibrated model record. In this analysis, we compare the results of the wasteload allocation scenario, which represents steady-state conditions where the total phosphorus point source load is always 5,699 pounds per year, to the historical model in which the total phosphorus point source load varies from year to year based on the historical data. The results from the model simulation are shown at key locations in the watershed, South Platte River at Chatfield Reservoir and Plum Creek at Chatfield Reservoir for total phosphorus (Table 7) and total flow (Table 8). Supplementary

model results are provided for the point source locations in Table 9 including, PCWRA (reach 52), Lockheed Martin (reach 16), Sageport (reach 116), and Waucondah (reach 113).

The model simulation shows there is an average annual increase in total phosphorus of approximately 620 pounds in the South Platte River and an average annual increase in total phosphorus of approximately 1,830 pounds in Plum Creek (Table 7). A more thorough analysis of the model results can be found in the *Discussion of Results* Section, where we compare the fractions of total phosphorus point source load that is transported to Chatfield Reservoir.

In Table 8, the simulated flows for the South Platte at Chatfield Reservoir and Plum Creek at Chatfield Reservoir are provided to show the increase in flow between the wasteload allocation scenario and the historical model results. In Table 9, we show the simulated total phosphorus loads for each reach where a point source discharges into the watershed. The table shows the wasteload allocation scenario, the historical scenario, and the difference between the two model scenarios. The results confirm that the largest increases in total phosphorus load occur in the reaches where the PCWRA and Lockheed Martin discharge into the watershed.

Table 7: Total Phosphorus Annual Wasteload Allocation at Chatfield Reservoir

| Year | Wasteload Allocation (lbs) | | Modeled Historical (lbs) | | Difference (lbs) (wasteload – historical) | |
|----------------|---|---|---|---|---|---|
| | South Platte at Chatfield Reservoir (Reach 16) | Plum Creek at Chatfield Reservoir (Reach 15) | South Platte at Chatfield Reservoir (Reach 16) | Plum Creek at Chatfield Reservoir (Reach 15) | South Platte at Chatfield Reservoir (Reach 16) | Plum Creek at Chatfield Reservoir (Reach 15) |
| 2000 | 6,020 | 6,940 | 5,610 | 4,110 | 410 | 2,820 |
| 2001 | 3,680 | 6,600 | 3,010 | 4,100 | 670 | 2,500 |
| 2002 | 4,080 | 4,810 | 3,550 | 3,090 | 530 | 1,720 |
| 2003 | 7,790 | 11,810 | 7,440 | 10,630 | 350 | 1,190 |
| 2004 | 7,310 | 7,570 | 7,050 | 6,870 | 270 | 700 |
| 2005 | 8,750 | 8,240 | 8,730 | 6,720 | 20 | 1,530 |
| 2006 | 4,690 | 7,470 | 4,310 | 5,610 | 380 | 1,870 |
| 2007 | 17,120 | 21,140 | 17,090 | 19,190 | 30 | 1,950 |
| 2008 | 4,930 | 6,590 | 4,020 | 5,110 | 920 | 1,480 |
| 2009 | 6,280 | 9,180 | 5,320 | 7,750 | 960 | 1,430 |
| 2010 | 5,840 | 17,490 | 4,860 | 15,260 | 970 | 2,220 |
| 2011 | 2,550 | 6,890 | 1,590 | 4,960 | 960 | 1,940 |
| 2012 | 1,630 | 6,130 | 680 | 4,420 | 950 | 1,720 |
| 2013 | 3,030 | 6,190 | 2,060 | 4,010 | 970 | 2,180 |
| 2014 | 6,920 | 7,260 | 5,950 | 5,070 | 970 | 2,190 |
| Average | 6,040 | 8,950 | 5,420 | 7,130 | 620 | 1,830 |

Table 8: Total Flow Annual Wasteload Allocation

| Year | Wasteload Allocation (acre-foot (af)) | | Modeled Historical (af) | | Difference (af) (wasteload – historical) | |
|----------------|---|---|---|---|---|---|
| | South Platte at Chatfield Reservoir (Reach 16) | Plum Creek at Chatfield Reservoir (Reach 15) | South Platte at Chatfield Reservoir (Reach 16) | Plum Creek at Chatfield Reservoir (Reach 15) | South Platte at Chatfield Reservoir (Reach 16) | Plum Creek at Chatfield Reservoir (Reach 15) |
| 2000 | 71,200 | 23,160 | 69,510 | 17,670 | 1,690 | 5,490 |
| 2001 | 52,910 | 19,390 | 51,260 | 14,210 | 1,650 | 5,180 |
| 2002 | 34,710 | 10,650 | 32,980 | 5,600 | 1,730 | 5,040 |
| 2003 | 53,520 | 30,330 | 51,960 | 25,610 | 1,560 | 4,730 |
| 2004 | 48,760 | 22,700 | 47,230 | 18,180 | 1,530 | 4,520 |
| 2005 | 76,180 | 29,400 | 74,780 | 25,190 | 1,400 | 4,220 |
| 2006 | 86,600 | 20,080 | 85,190 | 16,050 | 1,400 | 4,020 |
| 2007 | 258,780 | 65,650 | 257,230 | 62,000 | 1,550 | 3,650 |
| 2008 | 114,900 | 21,180 | 112,660 | 17,360 | 2,240 | 3,810 |
| 2009 | 113,850 | 30,010 | 111,610 | 26,560 | 2,240 | 3,450 |
| 2010 | 105,560 | 47,680 | 103,310 | 43,960 | 2,250 | 3,720 |
| 2011 | 61,860 | 17,050 | 59,600 | 13,400 | 2,260 | 3,650 |
| 2012 | 25,620 | 16,820 | 23,340 | 13,020 | 2,280 | 3,800 |
| 2013 | 55,900 | 17,010 | 53,630 | 13,720 | 2,270 | 3,300 |
| 2014 | 140,000 | 19,580 | 137,730 | 16,590 | 2,270 | 2,990 |
| Average | 86,690 | 26,050 | 84,800 | 21,940 | 1,890 | 4,100 |

Table 9: Total Phosphorus Annual Wasteload Allocation at Point Source Locations

| Year | Modeled Wasteload Allocation (lbs) | | | | Modeled Historical (lbs) | | | | Difference (wasteload – historical) | | | |
|----------------|------------------------------------|-----------------|--------------|------------|--------------------------|-----------------|--------------|------------|-------------------------------------|-----------------|-----------|------------|
| | PCWRA | Lockheed Martin | Sageport | Waucondah | PCWRA | Lockheed Martin | Sageport | Waucondah | PCWRA | Lockheed Martin | Sageport | Waucondah |
| 2000 | 6,330 | 6,020 | 610 | 470 | 3,270 | 5,610 | 540 | 120 | 3,070 | 410 | 70 | 360 |
| 2001 | 6,160 | 3,680 | 600 | 460 | 3,490 | 3,010 | 530 | 100 | 2,680 | 670 | 70 | 360 |
| 2002 | 5,240 | 4,080 | 290 | 410 | 3,560 | 3,550 | 220 | 50 | 1,670 | 530 | 70 | 360 |
| 2003 | 8,310 | 7,790 | 2,210 | 800 | 7,290 | 7,440 | 2,140 | 430 | 1,020 | 350 | 70 | 360 |
| 2004 | 6,750 | 7,310 | 640 | 480 | 6,330 | 7,050 | 570 | 120 | 410 | 270 | 70 | 360 |
| 2005 | 6,860 | 8,750 | 1,090 | 580 | 5,230 | 8,730 | 1,080 | 320 | 1,630 | 20 | 10 | 250 |
| 2006 | 6,630 | 4,690 | 1,080 | 560 | 4,680 | 4,310 | 1,070 | 310 | 1,960 | 380 | 10 | 250 |
| 2007 | 12,010 | 17,120 | 4,200 | 1,210 | 9,910 | 17,090 | 4,180 | 1,000 | 2,090 | 30 | 20 | 210 |
| 2008 | 6,140 | 4,930 | 550 | 470 | 4,520 | 4,020 | 530 | 310 | 1,620 | 920 | 20 | 150 |
| 2009 | 7,130 | 6,280 | 960 | 520 | 5,730 | 5,320 | 940 | 260 | 1,400 | 960 | 30 | 260 |
| 2010 | 10,050 | 5,840 | 3,420 | 1,090 | 7,630 | 4,860 | 3,390 | 820 | 2,420 | 970 | 30 | 260 |
| 2011 | 6,470 | 2,550 | 490 | 450 | 4,410 | 1,590 | 450 | 170 | 2,070 | 960 | 40 | 280 |
| 2012 | 5,970 | 1,630 | 430 | 440 | 4,180 | 680 | 380 | 150 | 1,790 | 950 | 50 | 290 |
| 2013 | 5,970 | 3,030 | 480 | 450 | 3,550 | 2,060 | 430 | 170 | 2,430 | 970 | 50 | 280 |
| 2014 | 6,600 | 6,920 | 520 | 460 | 4,220 | 5,950 | 480 | 190 | 2,380 | 970 | 40 | 270 |
| Average | 7,110 | 6,040 | 1,170 | 590 | 5,200 | 5,420 | 1,130 | 300 | 1,910 | 620 | 40 | 290 |

PCWRA is located in model Reach 52, Lockheed Martin is in Reach 16, Sageport is in Reach 116, and Waucondah is in Reach 113.

Discussion of Results

In model scenario 1) Watershed Simulated without Point Source Discharges (the no point source loading scenario) and model scenario 2) the Full Wasteload Allocation scenario, we consider three different iterations of point sources in the watershed and their total phosphorus loading implications for Chatfield Reservoir: no point sources in the watershed, historical point sources, point sources discharging with their full wasteload allocation. In these analyses we compare results using the modeling period of record (2000-2014), and a subset of the modeling period of record (2008-2014), which analyzes results after point source discharges from the Roxborough WWTF have ended. The recent modeling record (2008-2014) is helpful to demonstrate changes in the South Platte basin over time. See the *South Platte Historical Diversions* Section for further discussion of the Roxborough WWTF point source and historical diversions in the South Platte basin.

Point Sources and Watershed Loading

First, we examined how the point sources are represented in the Chatfield Reservoir watershed, by quantifying the total phosphorus load from the point sources as a fraction of the total phosphorus contributing to the reservoir (by subwatershed, South Platte versus Plum Creek). Note that this does not measure the relative contribution of total phosphorus from the point source to the reservoir (see the next section of the memorandum).

Equation 1:

$$\begin{aligned} & TP \text{ Point Source to Total TP Load (\%)} \\ &= \frac{\text{Historical TP Point Source}}{\text{Simulated TP to Chatfield Reservoir for Historical Scenario}} \end{aligned}$$

Equation 2:

$$\begin{aligned} & TP \text{ Point Source to Total TP Load (\%)} \\ &= \frac{\text{Full Wasteload TP Point Source}}{\text{Simulated TP to Chatfield Reservoir for Wasteload Scenario}} \end{aligned}$$

South Platte River

When the point sources are turned off, there are no point sources contributing total phosphorus to Chatfield Reservoir from the South Platte River. In the historical scenario the South Platte River point sources (Lockheed Martin and Roxborough) (24-524 lbs) represent 1-10% of the total phosphorus load from the South Platte River to Chatfield Reservoir (3500–5400 lbs) (depending on the period of record) (Equation 1).

In the full wasteload allocation scenario, the expanded Lockheed Martin point source (1,000 lbs) represents 17-23% of the total phosphorus load from the South Platte River to Chatfield Reservoir (4,500-6,000 lbs) (depending on the period of record). The new fraction of total phosphorus in the full wasteload allocation scenario is about 10-21% of the South Platte total phosphorus load to Chatfield Reservoir (depending on the period of record) (Equation 2). We

note that the Roxborough point source is off for the full wasteload allocation scenario since it is currently treated out of the basin (see Table 10).

Plum Creek

When the point sources are turned off, there are no point sources contributing total phosphorus to Chatfield Reservoir from Plum Creek. In the historical scenario the Plum Creek point sources (PCRWA, Sageport, and Waucondah) (2,500 lbs) represent 35% of the total phosphorus load from Plum Creek to Chatfield Reservoir (7,100 lbs) (Equation 1).

In the full wasteload allocation scenario, the expanded Plum Creek point sources (4,700 lbs) represent 52% of the total phosphorus load from Plum Creek to Chatfield Reservoir. The new fraction of total phosphorus in the wasteload allocation scenario is about 20% of the Plum Creek total phosphorus load to Chatfield Reservoir (9,000 lbs) (Equation 2) (see Table 11).

Fraction of New Point Source Load to Chatfield Reservoir

In the next analysis, we used the simulations to understand how changes to point source loads in the watershed relate to changes in the amount of total phosphorus delivered to Chatfield Reservoir. By analyzing the change in total phosphorus transitioning from a simulation without point source loading, to historical point source loading, to full wasteload allocation loading, we can better understand how future potential increases in total phosphorus loads in the watershed may be delivered to Chatfield Reservoir. These data represent the simulated effects of the new (incremental) total phosphorus point source load fraction that returns to Chatfield Reservoir.

Equation 3:

$$\begin{aligned} \text{New TP to Chatfield Reservoir (\%)} \\ = \frac{(\text{Simulation of Historical Load} - \text{Simulation without Point Sources})}{(\text{Observed Historical Load} - \text{Observed without Point Sources})} \end{aligned}$$

Equation 4:

$$\text{New TP to Chatfield Reservoir (\%)} = \frac{(\text{Simulated Wasteload} - \text{Simulated Historical Load})}{(\text{Observed Wasteload} - \text{Observed Historical Load})}$$

South Platte River

In the first model scenario (no point source loading), we compare the historical model simulation with a simulation that has point source discharges turned off. By analyzing the difference in total phosphorus loads between these two models we see that 69-97% of the total phosphorus point source load is released to Chatfield Reservoir (24-360 lbs of the 24-520 lbs of total phosphorus load is transported to the reservoir, depending on the period of record) (Equation 3) (see Table 10 for results).

Over the complete period of record (2000-2014) less of the total phosphorus is transported to the reservoir (69%) because of the active diversions in reach 29 that remove some of the total phosphorus discharged into the watershed by the Roxborough WWTF. In comparison, from

2008 to 2014, 97% of the total phosphorus is transported to the reservoir when all active point sources (Lockheed Martin) are located below the diversion structures.

In the second scenario (full wasteload allocation), we compare the historical model simulation with the maximum wasteload allocation simulation. In this model run, the wasteload is 1,006 pounds and the historical load is 24-525 pounds, so the new contributing load is 480-980 pounds. By analyzing the difference in total phosphorus loads between the two models we see that 97-100% of the new (incremental) total phosphorus point source load is released to Chatfield Reservoir (480-960 lbs of the 480-980 lbs of total phosphorus load is transported to the reservoir) (Equation 4) (see Table 10).

In the South Platte River, due to the location and timing of the Roxborough WWTF point source and historical diversions from the river (model reach 29), a comparison between the full wasteload scenario and the historical scenario needed to account for the changes in these conditions. Since the full wasteload scenario did not include the historical Roxborough point source (2000-2007), we had to account for its total phosphorus removal from the basin by the historical diversions (approximately 140 pounds annually 2000-2014) during the historical scenario when comparing it to the full wasteload scenario. Table 10 shows the average annual simulated point source at the reservoir (620 lbs, 2000-2014), the additional total phosphorus removed by the diversions when Roxborough WWTF is simulated (140 lbs, 2000-2014), and the final average annual point source simulated at the reservoir by the full wasteload scenario (480 lbs, 2000-2014).

Plum Creek

In the first model scenario (no point source loading), we compare the historical model simulation with a simulation that has point source discharges turned off. By analyzing the difference in total phosphorus loads between these two models we see that 69% of the total phosphorus point source load reaches Chatfield Reservoir (1,720 lbs of the 2,480 lbs of total phosphorus load is transported to the reservoir) (2000-2014) (Equation 3) (see Table 11).

In the second scenario (full wasteload allocation), we compare the historical model simulation with the maximum wasteload allocation simulation. In this model run, the wasteload is 4,700 lbs and the historical load is 2,480 lbs, so the new contributing load is 2,210 lbs. By analyzing the difference in TP loads between the two models we see that 83% of the Plum Creek total phosphorus point source load is released to Chatfield Reservoir (1,830 lbs of the new 2,210 lbs total phosphorus load is transported to the reservoir) (2000-2014) (Equation 4) (see Table 11).

Summary

The point sources along the South Platte River (Lockheed Martin and Roxborough WWTF) are relatively close in distance to Chatfield Reservoir with higher flow rates, and most of the incremental total phosphorus point source load is transported to Chatfield Reservoir. In the historical scenario 69-97% of the total phosphorus point source load is transported to the reservoir. Over the complete period of record (2000-2014) less of the total phosphorus is transported to the reservoir (69%) because of the active diversions in reach 29, that remove some phosphorus from the watershed. After the Roxborough WWTF stops discharging into the

watershed (2008-2014), 97% of the total phosphorus is transported to the reservoir because the remaining point source (Lockheed Martin) is located below both of the diversion structures. In the full wasteload allocation scenario 97-100% of the new total phosphorus is load transported to Chatfield Reservoir (see Table 10).

Table 10: South Platte River Total Phosphorus Point Source Loading

| | Historical Point Sources | | Full Wasteload | |
|---|--------------------------|-----------|----------------|-----------|
| | 2000-2014 | 2008-2014 | 2000-2014 | 2008-2014 |
| Total Point Source | | | | |
| Historical TP point source load (lbs) | 520 | 20 | 1,000 | 1,000 |
| Simulated TP load to Chatfield Reservoir (lbs) | 5,420 | 3,500 | 6,040 | 4,450 |
| TP Point Source / Total TP Load to reservoir (%) | 10% | 1% | 17% | 23% |
| New Point Source | | | | |
| New simulated TP point source load (lbs) | 360 | 20 | 620 | 960 |
| Reach 29 TP modeled historical diversion (lbs) (removed from river) | --- | --- | 140 | 0 |
| Revised simulated TP point source load (lbs) | 360 | 20 | 480 | 960 |
| New estimated TP point source load (lbs) | 520 | 20 | 480 | 980 |
| New TP to Chatfield Reservoir (%) | 69% | 97% | 100% | 97% |

The point sources in Plum Creek (PCWRA, Waucondah, and Sageport) are further upstream in the watershed from Chatfield Reservoir, with lower flow rates. In the first scenario (no point source to historical scenario) about 69% of the new total phosphorus load is transported to the reservoir, while in the wasteload allocation scenario about 83% of the new total phosphorus load is transported to Chatfield Reservoir (see Table 11).

Table 11: Plum Creek Total Phosphorus Point Source Loading

| | Historical Point Sources | | Full Wasteload | |
|--|--------------------------|-----------|----------------|-----------|
| | 2000-2014 | 2008-2014 | 2000-2014 | 2008-2014 |
| Total Point Source | | | | |
| Historical TP point source load (lbs) | 2,480 | 2,408 | 4,700 | 4,700 |
| Simulated TP load to Chatfield Reservoir (lbs) | 7,130 | 6,650 | 8,950 | 8,530 |
| TP Point Source / Total TP Load to reservoir (%) | 35% | 36% | 52% | 55% |
| New Point Source | | | | |
| New simulated TP point source load (lbs) | 1,720 | 1,650 | 1,830 | 1,880 |
| New estimated TP point source load (lbs) | 2,480 | 2,410 | 2,210 | 2,290 |
| New TP to Chatfield Reservoir (%) | 69% | 68% | 83% | 82% |

The total phosphorus point source loads are transported fairly efficiently to Chatfield Reservoir, with a large fraction of the new incremental load present as inflow to the reservoir. However, we note that the total phosphorus load in Plum Creek may have more opportunities for loss due to adsorption to sediment, deposition of adsorbed phosphorus, and uptake by algae, for example. Additionally for Plum Creek, in the full wasteload scenario (scenario 2), a larger fraction of the total phosphorus is transported to Chatfield Reservoir (83%) than from the first scenario (no point source to historical scenario) (69%), indicating there is less total phosphorus lost within the river reach. In the South Platte, both scenarios transported most of the total phosphorus point source load to the Chatfield Reservoir (97-100%), unless the point source load was upstream of the diversions in reach 29, in which case some of the total phosphorus load is removed from the basin.

References

- Chatfield Watershed Authority, 2021. 2021 Annual Report. Accessed September 2022. Available online <https://www.chatfieldwatershedauthority.org/annual-reports>.
- Leonard Rice Engineers and Lynker Technologies, 2016. Chatfield Watershed HSPF Model Report.